More than 25 years of flexibility · competence · reliability


Continuous Mixer



Continuous High-Speed Mixer SM 1

Continuous Mixer consisting of a mixing tube and a turbo mixer.

	Туре	Capacity to/h	A	C	D
ſ	SM-10	1 - 3	1200 + 1600		
	SM-11	5 - 6 (10)	2000	adjust	tment to
ſ	SM-12	8 - 15 (20)	2200	operatio	nal needs
	SM-13	20 - 30 (40)	2500 + 3000		






Continuous High-Speed Mixer SM 2

Continuous Mixer SM 2 in twinlink version, equipped with a conveyor screw and a mixing tube with turbo mixer.

Туре	Capacity to/h	A	В	C	D	
SM 20	1 - 3	1200	2000	adjustment to		
SM 21	3 - 6 (10)	2000	2500			
SM 22	8 - 16 (20)	2200		operation		
SM 23	20 - 35 (40)	2500-3000	up to 4000	oporational noods	iai noodo	
SM 24	40 - 50 (60)	3000	4000			






Continuous Three-Shaft Mixer DWM

equipped with separate premix worms for resin and hardener and a final mixer.

Туре	Capacity to/h	A	В	C	D	
DWM 0	1 - 3	1200	1500			
DWM 1	3 - 6 (10)	1600	1500	adjustment to		
DWM 2	8 - 16 (20)	1600	2000	operation	al needs	
DWM 3	20 - 35 (40)	1600	up to 3500		10000	
DWM 4	40 - 50 (60)	2000	3500			

- Working with binder having a viscosity ≤ 1600 cp
- Lowest consumption of binder
- Low wear thanks to low turning rates of the premix worms and the final mixer














Console Version, Movable Mixer

Continuous Mixer or Continuous Three-Shaft-Mixer (adjustable in height) equipped with stripping car and transfer hopper fixed on a travelling gear. The sand is continuously supplied by a belt conveyor.


The binder tanks are installed on the travelling gear.





Mobile Version, Movable Mixer


Continuous Mixer or Continuous Three-Shaft-Mixer (adjustable in height) equipped with a traveling gear on which sand bunkers and binder tanks are mounted. The sand supply is guaranteed by a filling station.





Mixer adjustable in height

Continuous Mixer or Continuous Three-Shaft-Mixer (adjustable in height) equipped with a hydraulically operating height adjustment (1-2 m) integrated in the pedestal.



Further versions on demand.

Hensel GmbH

Eisenhüttenstraße 26 D-57074 Siegen Germany Tel ++49 (0) 271 661 23-35 Fax ++49 (0) 271 61866 **www.hensel-giessereitechnik.de** info@hensel-giessereitechnik.de A Member of



Equipment Engineering · Plant Construction Industrial Fans